

Undercarriage Experts

Any Make, Any Model

Southeastern is your source for undercarriage parts & service

- Parts available for any undercarriage
- Parts delivery within 24 hours
- Factory trained technicians can service any make or model

Undercarriage Parts – For All Makes, All Models

- Sprockets
- Components
- Track links & chains
- Idlers
- Bushings
- Rollers
- Pins
- **And More!**



Undercarriage Inspections & Service

- Schedule regular inspections to spot operational or maintenance problems.
- Southeastern's technicians can estimate the remaining life of undercarriage parts with ultrasonic measurement tools, so you can plan for the downtime and expense of replacing components.

www.southeasternequip.com

- | | |
|---|---|
| Indiana
Evansville
812-476-7321
Fort Wayne
260-483-8868
Indianapolis
317-872-4877 | Kentucky
Burlington
859-586-6133
Michigan
Holt
517-694-0471
Novi
248-349-9922 |
| Ohio
Brilliant
740-598-3400
Brunswick
330-225-6511
Cambridge
740-432-6303
Dublin
614-889-1073
Gallipolis
740-446-3910
Heath
740-522-3500 | Mansfield
419-529-4848
Marietta
740-374-7479
Mentor
440-255-6300
Monroe
513-539-9214
North Canton
330-494-3950
Perrysburg
419-874-0331 |

Undercarriage Maintenance Tips

Extend the life of your undercarriage by following a few simple rules.

Minimize high operating speeds

Higher speeds cause more wear on the undercarriage. Use the slowest possible operating speed for the job.

Alternate the turning direction

Continuous turning to the same side can cause asymmetrical wear and accelerate wear for sprocket teeth, track tread, guide lugs and roller flanges.

Inspect your equipment visually every day for signs of wear


Check for cracks, bends and breaks on components. Look for wear on bushings, sprockets and rollers. If you see any components that are shiny, there's probably an alignment problem. Make sure nuts and bolts are not loose, which can cause abnormal wear by interfering with proper movement of parts.

Control track spinning when filling the bucket

Use loader hydraulics to penetrate into the material to reduce track spinning. Unnecessary spinning of the tracks can accelerate wear and cause cuts in the tracks.

Use the narrowest shoe possible

Wider shoes can cause problems maneuvering by sticking out farther and making it more difficult to turn. Wider shoes may be necessary, however, to keep the machine from sinking in extremely wet conditions.



Schedule an undercarriage inspection today!